

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
13 March 2003 (13.03.2003)

PCT

(10) International Publication Number  
**WO 03/020545 A1**

- (51) International Patent Classification<sup>7</sup>: **B60K 37/00**
- (21) International Application Number: **PCT/US02/27859**
- (22) International Filing Date:  
3 September 2002 (03.09.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/316,682 31 August 2001 (31.08.2001) US
- (71) Applicant (for all designated States except US): **JOHNSON CONTROLS TECHNOLOGY COMPANY** [US/US]; 49200 Halyard Drive, Plymouth, MI 48170 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **TUBIDIS, Athanasios, L.** [GR/GR]; 5, Lefkosias St., 55133 Thessaloniki (GR). **FARBER, James, J.** [US/US]; 95 West 20th Street, Holland, MI 49423 (US). **KRSTESKI, John** [US/US]; 3100 Harrow Way, Shelby Township, MI 48316 (US). **RINGOLD, Ted, W.** [US/US]; 1532 Sunflower Way, Hudsonville, MI 49426 (US). **CENTELLAS, Samuel** [US/US]; 1090 Curwood, Saginaw, MI 48609 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE (utility model), DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- with international search report
  - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

WO 03/020545 A1

(54) Title: CONFORMABLE VEHICLE DISPLAY

(57) Abstract: A conformable vehicle display includes a flexible display screen coupled to a substrate. The substrate is a curved transparent substrate that is adapted to be coupled to a vehicle component having a curved exterior surface. The flexible display screen is at least partially separate from the exterior surface of the vehicle component and has a luminescent display. The exterior surface of the vehicle component is visible through the flexible display screen and the substrate when the flexible display screen is not activated. The flexible display screen may be a transparent organic light emitting diode display device.

## CONFORMABLE VEHICLE DISPLAY

### FIELD OF THE INVENTION

[0001] The present invention relates generally to the art of displays and more specifically to displays used in vehicle interiors. Still more specifically, the present invention relates to displays which may be applied to a variety of vehicle interior surfaces, such as the instrument panel, consoles, and the like, and wherein the displayed information can be pictures, numerical data, warning information, educational or entertainment material, and other information useful to the vehicle's driver and/or to passengers.

### BACKGROUND OF THE INVENTION

[0002] A wide variety of information about a vehicle, its performance, maintenance, orientation, and the condition of its numerous systems (fuel, door closure, temperature) and the like have been collected and displayed within vehicle interiors for many years. In recent years, with technology developments accelerating at heretofore unbelievable rates, the types of information collected, the accuracy thereof and the methods for displaying the information have also been increasing. Examples include compass and mirror technology and the combination thereof, where compass headings are displayed on the surface of the vehicle interior.

[0003] These various examples of information collection and/or display are provided purely for purposes of establishing a general background from which the display improvement of the present invention can be appreciated. At present, the displays themselves, wherever they have been located, involve hardware and systems which are typically designed for specific applications for

reasons of size, attachment, supplying power thereto or the like. Little flexibility currently exists for using conformable display surfaces in a variety of vehicle locations. Further, other conventional display technology (e.g., liquid crystal display ("LCD"), light emitting diode ("LED"), etc.) incorporate a lens and is located in a module (e.g., wherein the lens is a first or exterior surface and the display is a second or inner surface). (The lens is typically used to cover or obscure circuit boards and the like.) Additionally, conventional display technology (particularly LCD displays) are only used in a flat and/or non-flexible surface application.

[0004] To provide a reliable, widely adaptable, self-illuminating vehicle display that is less expensive, has higher contrast, and uses less energy than conventional displays (e.g., LCDs, and the like) and avoids the above-referenced and other problems would represent a significant advance in the art.

### SUMMARY OF THE INVENTION

[0005] A primary feature of the present invention is to provide a vehicle display which provides interior designers with enhanced flexibility and aesthetics.

[0006] Another feature of the present inventions is to provide a display system which requires little space and which may be located in a wide variety of locations within a vehicle interior.

[0007] Another feature of the present inventions is to move the display to the first surface and provide a vehicle display that does not require a lens.

[0008] A different feature of the present inventions is to provide a display which may be placed over, rather than within, a vehicle interior component and may resemble a contoured surface profile.

**[0009]** Yet another feature of the present inventions is to provide a display surface which yields a high quality display of any one or more kinds of data, including but not limited to safety, vehicle condition, entertainment, educational and status data.

**[0010]** Another feature of the present inventions is to provide a display which may be installed using assembly techniques which are commonly used to install trim covers, including installation on curved surfaces, whether they be convex or concave.

**[0011]** How these and other objects of the present inventions are accomplished, individually, collectively or in various subcombinations will be described in the following detailed description of preferred and alternate embodiments, taken in conjunction with the FIGURES. Generally, however, they are accomplished by using a thin, flexible display screen or sheet (such as organic light emitting diode ("OLED"), LCD material, flexible LCD, thin film electro-luminescent ("TFEL"), or other suitable display technology, and preferably organic sheet of light-emitting diode material. The display may be in any shape (e.g., square, circular, oval, etc.) and may be applied over a variety of interior surfaces, including but not limited to the instrument panel, consoles, door, pillar, side trim panels, etc. More than one such display sheet may be employed for displaying the same or different information. The display screen can be the first surface (e.g., the exterior surface exposed to the passenger compartment), recessed behind a plastic (protective) substrate, sprayed or poured into a recess (e.g., OLED), insert molded, etc. The information displays can be fixed in place using the same trim hardware as is currently used to cover the pillar with leather, vinyl, fabric, foam and other cover materials. Alternatively, the display sheet may be attached using mechanical

fasteners (such as snaps, screws, clips, etc.), other fasteners (such as Velcro® hook and loop fasteners), sewing, adhesives, etc. Also, the display sheet can be insert molded along with a fabric material or other aesthetic or functional article. This ease of assembly makes adoption of the display to different types or sizes of vehicles much easier than would be the case in conventional applications (e.g., if deep recesses, holes, apertures, etc. were required to receive thicker display devices). Also, protecting the display is intended to enhance reliability and reduce cost associated with damaged displays. The color of the display sheet can also be coordinated with the remainder of the vehicle interior. Other ways in which the various features of present invention can be accomplished will be described later herein, and still others will appear to those skilled in the art after they have read this specification. Such other ways are deemed to fall within the scope of the present invention, if they fall within the scope of the claims which follow. Additionally, the displayed image may be provided by ultraviolet ("UV") light being projected through a substrate with or without an insert or over-molded fabric.

**[0012]** The present invention further relates to various features and combinations of features shown and described in the disclosed embodiments. Other ways in which the objects and features of the disclosed embodiments are accomplished will be described in the following specification or will become apparent to those skilled in the art after they have read this specification.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

**[0013]** The invention will become more fully understood from the following detailed description taken in conjunction with the accompanying drawings, wherein like reference numerals refer to like elements, in which:

[0014] FIG. 1 is a perspective view of a vehicle and instrument panel having various vehicle display options;

[0015] FIG. 2 is a perspective view of an instrument panel having a vehicle display;

[0016] FIG. 3 is a schematic representation of information that may be depicted on a vehicle display;

[0017] FIG. 4 is a schematic representation of information that may be depicted on a vehicle display;

[0018] FIG. 5 is a partial schematic sectional view of a substrate having a display screen;

[0019] FIG. 6 is an exploded sectional view of a vehicle display having a substrate, display screen, and a fabric layer; and

[0020] FIG. 7 is a partial sectional view of a vehicle display having a substrate and a display screen.

#### **DETAILED DESCRIPTION OF PREFERRED AND OTHER EXEMPLARY EMBODIMENTS**

[0021] Before beginning the detailed description of the preferred and alternate embodiments of the present inventions, several general comments can be made about the applicability and scope thereof. First, as indicated above, the location of the display of the invention may be widely varied, and, in fact, can be on practically every interior trim surface. Examples, for illustration purposes rather than by way of limitation, include the instrument panel, the steering column, overhead systems (including the headliner or sun-roof cover, etc.), consoles, door, window, windshield, etc.



**[0022]** Second, the number of displays can vary. For example, a display may be provided for the driver, while instrument panel and/or seat displays may be provided for first or second row passengers. Since the number of displays can be varied, the types of data or information displayed thereon can also be varied, so that each display screen or sub-grouping of display screens can show different information.

**[0023]** Third, a preferred screen material is a flexible, organic LED (OLED) screen such as that available from Pioneer, Kodak, DuPont, or Philips. (Alternatively, the flexible LCD is available from Philips, and the TFEL is available from Planas.) Such OLED display screens may be transparent, such as a transparent organic light emitting device available from Universal Display Corporation that is used in an exemplary embodiment. The primary attributes of display screens of the present inventions are that they be thin, flexible (or moldable) enough so that they may be applied to either planar or curved surfaces and that they provide sufficient clarity of the information or data to be displayed. Black and white, other monochromatic displays, or full color display screens are within the scope of the present invention.

**[0024]** Fourth, the manner of attachment of the display to the vehicle interior can also be widely varied. Several non-limiting examples are described here. One could be a generally planar display that replaces conventional cockpit clusters. Another would be a curved (almost semi-circular) display screen adapted to be coupled to the interface between the windshield and the dashboard or to the dashboard. The back side of the screen is shaped to match the exterior surface of the pillar facing the driver. The screen can be held in place using trim fastener strips or other components known in the vehicle art, and in an especially

preferred embodiment is affixed to the pillar at the same time the remaining trim is applied, thereby eliminating the need for an additional manufacturing step. A display screen of the present invention can also be adhered (using a suitable adhesive, e.g., a liquid adhesive), sewn, clipped, snapped or fastened to the desired interior surface either during initial fabrication or in a separate, subsequent step. Two-part fasteners, e.g., Velcro® hook and loop fasteners, can be used for the removable attachment of the display screen to the trim surface.

[0025] Fifth, the source and type of information to be displayed on the displays of the present invention can also be varied widely. One example is to provide the driver with vehicle information collected inside or outside of the vehicle. Another example is to provide vehicle performance (e.g., speed, RPM, etc.) information to the driver. Both of these examples have the obvious advantage of eliminating the need for the driver to look and search downward to observe this type of information, thereby decreasing the likelihood that an accident would occur resulting from the driver's eyes being taken "off the road." Other examples include providing the display of vehicle condition (e.g., temperature, heading, fuel levels, etc.), ambient conditions (e.g., temperature), safety information (e.g., tire pressure or wear, low fuel, overheating, low oil, excessive speed, tire slippage, etc.). Other uses for the display of the present invention are also included and will be readily appreciated by present and future vehicle designers after they read this specification.

[0026] Sixth, the particular type of data gathering, generating or processing can vary as widely as the types of information. For example sensors can be used to capture internal or external information which are then processed for display on the display screen. The information gathering, generating or

processing systems, in and of themselves, do not form part of the present invention. They can be self powered (e.g., by one or more batteries), solar powered, or coupled to the vehicle's electrical system.

**[0027]** Referring to FIGURES 1 and 2, a vehicle 10 with a passenger compartment 12 includes an instrument panel or dashboard 14, a steering wheel assembly 16, and a plurality of information displays (shown as an information display 18, a forward information display 20, and a dashboard information display 22). According to a preferred embodiment, the information displays described herein are configured to replace conventional analog and liquid crystal display ("LCD") instrument panels,

**[0028]** According to an exemplary embodiment, an instrument panel cluster (shown as information display 18) is coupled to dashboard 14 and configured to integrate vehicle or environmental information (e.g., tachometer, speedometer, and the like) (see FIGURE 3). Information display 18 is moveable between a stowed position (where display and dashboard 14 provides general planer surface) and a operational or deployed position (FIGURES 1 and 2). According to a preferred embodiment, information display 18 incorporates organic light emitting device ("OLED") technology. The OLED is made from a series of organic, thin films between a pair of conductors. When electrical current is applied to the conductors, light is emitted. Information display may be monochrome or color. According to a preferred embodiment, information display 18 incorporates transparent OLED technology so that information display 18 can be transparent or translucent (e.g., tinted).

**[0029]** According to an exemplary embodiment, a screen 31, which may have OLED technology, is mounted on a rigid substrate 24, which is

configured to support the screen 31 and to provide protection to the OLED itself (see for example FIGURE 7). According to a preferred embodiment, information display 18 includes a frame 32 (which may be located on 1 or more sides of information display 18), a pivot 34, and a ribbon cable (or over-molded wires, screened-on circuits, and the like) configured to provide data and power to the OLED. According to a preferred embodiment, a tachometer and speedometer use digital technology to graphically represent analog information (e.g., digital animation of analog gauges). The OLED information display 18 digitally integrates the tachometer and the speedometer into the same graphic image or scheme, thereby transferring the conventional analog information to a digital representation. The display of the tachometer and speedometer can be related in a continuous image and communicated simultaneously (e.g., sharing a common linear line and digitized analog "needles" that are shaped based on the relative road and engine speed data and their mathematical relationship). According to a preferred embodiment, information display is rotated to approximately 65 degrees. Alternatively, the information display can be configured to be angled at any of a variety of orientations.

**[0030]** Referring to FIGURES 1 and 4, forward information display 20 is located at the interface of dashboard 14 and the windshield 26, and is configured to provide vehicle or environmental information such as navigation information (e.g., a map, directions, compass information and the like, which can be tied to a global positioning satellite ("GPS") system), environmental information (e.g., current weather information, forecast information, and the like), vehicle information (e.g., system status, open door information, wheel air pressure, fuel level, oil pressure, battery charge information, and the like), business operation

(e.g., stock information and the like), entertainment information (e.g., volume, radio or recorded information, and the like), etc.

**[0031]** According to a preferred embodiment, forward information display 20 incorporates OLED technology. Preferably, OLED technology is coupled (e.g., bonded, fastened, insert molded, etc.) to or into a rigid substrate (e.g., translucent or transparent). The substrates 24 or 28 can be any of a variety of moldable materials. Preferably, substrates 24 or 28 are acrylic, polycarbonate, or other clear moldable material. Alternatively, substrates 24 or 28 are tinted. Alternatively, the OLED sheet or screen can provide the first surface (i.e., exposed to the interior of the vehicle), which may be held in a frame or mounted to a substrate. Alternatively, the OLED material is sprayed or poured into a recess in the substrate. Alternatively, the OLED screen is insert molded with the substrate, which may also include a fabric material or other material insert molded therewith. FIGURE 5 shows the screen 31 disposed on surface of substrate 28, but in other embodiments the screen may be insert molded to be placed in a center region of the substrate.

**[0032]** According to an alternative embodiment, forward information display 20 includes rear projection technology that is configured to display the information on a rigid substrate 28. As shown in FIGURE 1, forward information display 20 is disposed at the interface between windshield 26 and dashboard 14. Alternatively, forward information display 20 can extend up along or towards windshield 26 (e.g., when substrate 28 is transparent to provide full viewing access).

**[0033]** Referring to FIGURES 1 and 2 dashboard information display 22 is configured similar to forward information display 20. According to a

preferred embodiment, dashboard information display 22 incorporates OLED technology. Preferably, OLED technology is coupled (e.g., bonded, fastened, insert molded, etc.) to or into a rigid substrate (e.g., translucent or transparent). The substrates 24 or 28 can be any of a variety of moldable materials. Preferably, substrates 24 or 28 are acrylic, polycarbonate, or other clear moldable material. According to an alternative embodiment, dashboard information display 22 incorporates rear projection technology. Dashboard information display 22 may be configured to display any of a variety of vehicle or environmental information (e.g., such as that discussed above with regard to forward information display 20).

**[0034]** According to an alternative embodiment, information display 18, forward information display 20, and/or dashboard information display 22 incorporate insert molded fabric 29 configured to provide a textured or aesthetic appearance. Referring to FIGURE 6, according to an exemplary embodiment, the screen 31 disposed in a recess 30 in substrate 28 prior to fabric being integrally molded with substrate 28. Alternatively, the OLED is integrally molded with the substrate, which may also include a fabric material or other material insert molded therewith.

**[0035]** According to an alternative embodiment, the vehicle information displays (e.g., information display 18, forward information display 20, and/or dashboard information display 22) incorporates ultraviolet ("UV") reflective technology, which uses UV reflective or responsive symbols in the interior of the vehicle that are illuminated by UV lights which are configured to illuminate the pertinent graphic symbols (e.g., warning lights and the like).

**[0036]** According to an alternative embodiment, the fabric wrapped substrate or fabric insert-molded substrate is configured to allow the image to be

projected therethrough (e.g., rear projected). The image may be configured to project through the fabric, whereby the fabric is capable of allowing the light to "perforate" through. The image may be projected from inside of the instrument panel or dashboard, which eliminates the conventional LCD screen and its protective lens. As such, the display provides structural support to the passenger compartment interior but still "thin" (or otherwise dimensional) to the image or light to project through.

[0037] It is also important to note that the construction and arrangement of the elements of the OLED vehicle display as shown in the preferred and other exemplary embodiments is illustrative only. Although only a few embodiments of the present inventions have been described in detail in this disclosure, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter recited. For example, elements shown as integrally formed may be constructed of multiple parts or elements shown as multiple parts may be integrally formed, the operation of the interfaces (e.g. clamps, etc.) may be reversed or otherwise varied, the length or width of the structures and/or members or connector or other elements of the system may be varied, the nature or number of adjustment positions provided between the elements may be varied (e.g. by variations in the number of engagement slots or size of the engagement slots or type of engagement). It should be noted that the elements and/or assemblies of the system may be constructed from any of a wide variety of materials that provide

sufficient strength or durability, in any of a wide variety of colors, textures and combinations. It should also be noted that the display system may be used in association with a dynamic display, or alternatively other, fixed and non-movable displays or any of a wide variety of other surfaces in any of a wide variety of other applications. Accordingly, all such modifications are intended to be included within the scope of the present inventions. Other substitutions, modifications, changes and omissions may be made in the design, operating conditions and arrangement of the preferred and other exemplary embodiments without departing from the spirit of the present inventions.



**IN THE CLAIMS:**

- 1           1.     A conformable vehicle display, comprising:  
2                 a curved transparent substrate adapted to be coupled to a vehicle  
3     component having a curved exterior surface; and  
4                 a flexible display screen coupled to the substrate, at least a portion of  
5     the display screen being separate from the exterior surface of the vehicle  
6     component, the flexible display screen having a luminescent display;  
7                 wherein the exterior surface is visible through the flexible display  
8     screen and the substrate when the flexible display screen is not activated.
  
- 1           2.     The conformable vehicle display of claim 1, wherein the flexible  
2     display screen is a matrix display.
  
- 1           3.     The conformable vehicle display of claim 2, wherein the flexible  
2     display screen comprises an organic light emitting diode display.
  
- 1           4.     The conformable vehicle display of claim 3, wherein the flexible  
2     display screen comprises a transparent organic light emitting diode display.
  
- 1           5.     The conformable vehicle display of claim 1, wherein the  
2     exterior surface of the vehicle component comprises a fabric.
  
- 1           6.     The conformable vehicle display of claim 1, further comprising  
2     a trim layer incorporated into the substrate between the vehicle component and the  
3     flexible display screen.
  
- 1           7.     The conformable vehicle display of claim 6, wherein the trim  
2     layer is molded into the substrate.
  
- 1           8.     The conformable vehicle display of claim 7, wherein the trim  
2     layer is a fabric material.

- 1                   9.     The conformable vehicle display of claim 1, wherein the vehicle  
2     component is an instrument panel, a door, a pillar, or a side trim panel.
- 1                   10.    The conformable vehicle display of claim 1, wherein the  
2     substrate comprises acrylic.
- 1                   11.    The conformable vehicle display of claim 1, wherein the flexible  
2     display screen is coupled to a surface of the substrate facing the vehicle interior.
- 1                   12.    The conformable vehicle display of claim 11, wherein the  
2     flexible display screen is fastened to the substrate.
- 1                   13.    The conformable vehicle display of claim 1, wherein the flexible  
2     display screen is incorporated into the substrate.
- 1                   14.    The conformable vehicle display of claim 13, wherein the  
2     flexible display screen is disposed in a recess in the substrate.
- 1                   15.    The conformable vehicle display of claim 13, wherein the  
2     flexible display screen is insert molded into the substrate.
- 1                   16.    A vehicle instrument panel, comprising:  
2         a curved base surface;  
3         a fabric layer coupled to the base surface;  
4         a transparent curved substrate coupled to the base surface above the  
5     fabric layer; and  
6         a flexible transparent organic light emitting diode display screen  
7     coupled to and matching the curvature of the substrate above the fabric layer,  
8     wherein the fabric layer is visible when the display screen is off.
- 1                   17.    The vehicle instrument panel of claim 16, wherein the organic  
2     light emitting diode display is incorporated into the substrate.

1                    18.    The vehicle instrument panel of claim 17, wherein the organic  
2    light emitting diode display is disposed in a recess in the substrate.

1                    19.    The vehicle instrument panel of claim 16, wherein the organic  
2    light emitting diode display is insert molded into the substrate.

1                    20.    The vehicle instrument panel of claim 16, wherein the organic  
2    light emitting diode display is coupled to a surface of the substrate facing an interior  
3    compartment of a vehicle.

1                    21.    The vehicle instrument panel of claim 20, wherein the organic  
2    light emitting diode display is fastened to the substrate.

1                    22.    A method of making a vehicle display, comprising the steps of:  
2                    providing a vehicle component, a transparent curved substrate, and a  
3    flexible light emitting display;  
4                    coupling the light emitting display to the substrate; and  
5                    coupling the substrate to a textured exterior surface of the vehicle  
6    component.

1                    23.    The method of claim 22, further comprising the step of molding  
2    the light emitting display into the substrate.

1                    24.    The method of claim 22, further comprising the step of molding  
2    a fabric layer into the substrate between the flexible light emitting display and the  
3    exterior surface.


1                    25.    The method of claim 22, further comprising the step of creating  
2    a recess in the substrate, wherein the light emitting display is coupled to the  
3    substrate by placement into the recess.


1                    26.    The method of claim 22, wherein the light emitting display  
2    comprises an organic light emitting diode display.


1                   27.    The method of claim 22, wherein the exterior surface of the  
2 vehicle component is fabric.

1                   28.    The method of claim 22, further comprising the step of  
2 providing a fabric layer incorporated into the substrate between the vehicle  
3 component and the flexible display screen.

1                   29.    The method of claim 22, wherein the vehicle component is an  
2 instrument panel.








Captain's primary display  
Technology is used to enhance the sensory and social experience of driving  
Focus on creating an experience that is heightened and not inhibited through the overload of information management

FIGURE 3

# Ariston

far forward configurable display



Multiple use features combined into single products without being feature-laden.

So that consumers have a better tool of managing information overload

FIGURE 4






FIGURE 5




FIGURE 6




FIGURE 7

# INTERNATIONAL SEARCH REPORT

International Application No  
PC 1, US 02/27859

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 B60K37/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B60K G01P G09F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 197 08 610 A (SIEMENS AG) 24 September 1998 (1998-09-24)  column 1, line 29 -column 1, line 50 column 2, line 47 -column 2, line 55 column 3, line 22 -column 3, line 49; figures	1-4, 9, 11, 12, 22, 26, 29
X	US 5 834 893 A (FORREST STEPHEN R ET AL) 10 November 1998 (1998-11-10) column 1, line 29 -column 1, line 33 column 2, line 7 -column 2, line 15; claims 3, 7, 8	1-4, 22
A		16
X	US 5 844 363 A (FORREST STEPHEN R ET AL) 1 December 1998 (1998-12-01) claims 2, 12, 13	1-4

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*8\* document member of the same patent family

Date of the actual completion of the international search

19 December 2002

Date of mailing of the international search report

30/12/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Kyriakides, L

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 02/27859

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 19708610	A	24-09-1998	DE 19708610 A1	24-09-1998
			AU 7029398 A	22-09-1998
			WO 9839176 A1	11-09-1998
			EP 0964800 A1	22-12-1999
			JP 2001513911 T	04-09-2001
US 5834893	A	10-11-1998	AU 5621598 A	17-07-1998
			AU 5721098 A	17-07-1998
			CN 1245581 A	23-02-2000
			EP 0956741 A1	17-11-1999
			EP 0950254 A1	20-10-1999
			JP 2001507503 T	05-06-2001
			JP 2001527688 T	25-12-2001
			TW 385620 B	21-03-2000
			TW 379514 B	11-01-2000
			WO 9828947 A1	02-07-1998
			WO 9828767 A1	02-07-1998
US 5844363	A	01-12-1998	AU 4048897 A	06-03-1998
			BR 9711155 A	17-08-1999
			CN 1230288 A	29-09-1999
			EP 0946958 A1	06-10-1999
			JP 2000516761 T	12-12-2000
			KR 2000029979 A	25-05-2000
			WO 9807173 A1	19-02-1998
			US 2002058103 A1	16-05-2002

